

Product profile

IP2L

Snap-on LF/UHF
RFID Reader



- Easy snap-on installation to Intermec CN70 and CN70e mobile computers
- UHF RFID protocol support (EPCglobal Class 1 Gen 2, 902-928 MHz)
- LF RFID protocol support (TI TIRIS, 134.2 kHz)
- Adds RFID functionality without compromising any computer features, including all wireless network options
- Powered from the host computer, no additional battery required
- Pass-through connection enables docks and chargers without removing the reader module
- Optional UL Class I, Division 2, non-incendive (NI) rated configuration

The Intermec IP2L LF/UHF RFID reader is a snap-on peripheral for the Intermec CN70 and CN70e mobile computers, providing dual UHF and LF RFID capability. As a leader in RFID technology and rugged mobile computers, Intermec continues to enable comprehensive automatic identification and data capture (AIDC) solutions with mobile RFID. For asset tracking and maintenance verification applications, either inside the four walls or in the field, the IP2L enables short-range LF or UHF RFID reading without compromising the full feature set of the CN70 and CN70e mobile computers, including advanced bar code scanning, GPS location association, and communication via multiple network radios, including the latest wireless WAN (cellular) technologies.

The durable IP54 environmental rating and optional UL Class I, Division 2 non-incendive configuration allows the IP2L to be used in rough, demanding field environments. Combining two RFID technologies, the IP2L supports traditional LF and UHF applications and mixed environments

of both tag types, making the IP2L ideal for mobile, field-based asset tracking and maintenance verification solutions in oil and gas, heavy industrial and other field service market segments.

As a snap-on module, the reader can be added to an existing fleet of mobile computers without compromising any of the features of the host mobile computer. With support for Wi-Fi and wireless WAN connectivity through the CN70 or CN70e mobile computer, the IP2L supports a data connection nearly anywhere and enables GPS location association for real-time asset, source and service tracking.

The IP2L adds to Intermec's comprehensive line of mobile RFID readers. The reader is suitable for short-range applications where WWAN network connectivity is required. For long-range applications, the IP30 handheld RFID reader is best suited, and for medium to long-range applications that do not require WWAN, the 70 Series RFID is the ideal family of fully-integrated RFID-enabled mobile computers.

Physical Description

The IP2L Snap-on LF/UHF RFID Reader enables short-range LF and UHF RFID reading without compromising the full feature set of the Intermec CN70 or CN70e mobile computer, including wireless WAN connectivity. The IP2L has an NI rated option and meets FCC compliance standards for use in the US and Canada.

Physical Characteristics (without handheld computer)

Dimensions (L x W x D): 6.38 x 7.95 x 3.4 cm
(2.51 x 3.13 x 1.34 in)

Weight: 112.6 gm (4 oz)

Environmental Specifications

Operating Temp: -20° C to 50° C NI/60° C non-NI
(-4° F to 122° F NI/140° F non-NI)

Storage Temp: -30° C to 70° C (-22° F to 158° F)

Humidity: 10 to 95% (non-condensing)

Enclosure: IP54 compliant

Drop Survival: Withstands 4 foot drop (1.3m) 26 times to concrete Mil-Std-810F

Non-incendive (NI) Option*: Class I, Division 2, Groups A, B, C, D

Handheld Computer Compatibility

Supported Models: Intermec CN70, CN70e, CN70 NI*, CN70e NI* (all options)

Attachment: Snap-on to host computer with latching arms

Communication Interface: USB docking interface to host computer

Docking: Maintains docking capability with the Intermec FlexDock Modular Docking System for charging and Ethernet connectivity

Power: Powered from host computer

LED indicators: Read and write notifications available through host computer LED

UHF RFID Reader

Frequency: UHF 902-928 MHz

Tag Protocol Support: EPCglobal Class 1 Generation 2/ ISO 18000-6C (read and write)

RF Output Power: 6 to 25 dBm

Antenna Orientation: Forward-facing directional, radiating from the back plane of the reader.

Typical Read Range (tag dependent): Up to 45 cm (18 inches)

LF RFID Reader

Frequency: LF 134.2 kHz (half duplex)

Tag Protocol Support: Texas Instruments TIRIS (read only)

Typical Read Range (tag dependent): Up to 3 cm (1 inch)

Software

Use of this snap-on with the CN70/70e requires OS version 1.50.19.0013 or higher

Demonstration software available

Common Basic Reader Interface (BRI) API with

Intermec's RFID reader portfolio

Part Numbers

NI Rated*: 850-832-0xx

Non-NI Rated: 850-832-5xx

* For NI environments, customers must use both the NI-rated IP2L and an NI-rated CN70 or CN70e

North America

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348 2600
Fax: (425) 355 9551

North Latin America

Mexico
Phone: (+52) 55 52 41 48 00
Toll Free NOLA:
01800 490 4990

South Latin America

Brazil
Phone: (+55) 11 3711 6770
Fax: (+55) 11 5502 6780

Europe, Middle East & Africa

Reading, United Kingdom
Phone: (+44) 118 923 0800
Fax: (+44) 118 923 0801

Asia Pacific

Singapore
Phone: (+65) 6303 2100
Fax: (+65) 6303 2199

Media Sales

EMEA: (+31) 24 372 3167
USA: (513) 874 5882
<http://intermec.custhelp.com>

Sales

Toll Free NA: (800) 934 3163
Toll in NA: (425) 348 2726
Freephone ROW:
00800 4488 8844

OEM Sales

Phone: (425) 348 2762

Customer Service & Support

Toll Free NA: (800) 755 5505
Toll in NA: (425) 356 1799
EMEA: intermec.custhelp.com

Internet

www.intermec.com

Worldwide Locations

www.intermec.com/locations