



OMNIKEY[®] 3021 USB Reader



PORTABLE SMART CARD READER


- **Easy to install** – Eliminates the need to install drivers; uses native supported CCID drivers within the operating system.
- **Readily Compliant** – Meets all relevant industry standards for smooth integration in PC environment
- **Portable Form Factor** – Unique size makes it an ideal reader for large-scale deployments and mass distribution
- **Suits Any Application** – Compatible with virtually any smart card and major PC operating system

The OMNIKEY[®] 3021 is a high-performance, USB smart card reader that features all the trusted performance of OMNIKEY readers in a new and smaller form factor. Compliant with all industry standards, this reader is compatible with virtually any contact smart card, operating system and a variety of applications. This handy USB reader is the ideal choice for

large-scale deployments with any type of contact smart card or application software. The 3021 can be easily distributed together with any smart card, including credit cards, e-ID cards or software for other applications.

FEATURES:

- Meets major standards, including ISO 7816, EMVCo Terminal 1, USB CCID, PC / SC and HBCI (Home Banking Computer Interface)
- Usage within an application is based on standardized interfaces like PC / SC
- USB CCID support makes integration into an existing system the easiest ever by connecting host and smart card reader without the need for additional drivers
- Attractive, small size fits in an envelope to distribute with smart card, credit card, e-ID card or software for online banking or digital signature applications
- All major operating systems supported
- Meets GSA FIPS 201 requirements
- Supports high-speed data transmission
- UPC barcode for easier logistics



SPECIFICATIONS

Base Model Number	OMNIKEY® 3021
Card Size	SMART CARD INTERFACE ID-1 (Full size)
Standards	ISO 7816
Supported Card Types	Class A: 5V @ 60 mA; Class B: 3 V @ 60 mA; Class C: 1.8V @ 35 mA ATR response time up to 1.6 s
Protocols	Asynchronous: T=0; T=1 Synchronous: S=8 (I ² C); S=9 (3-wire); S=10 (2-wire)
Insertion Cycles	100,000
Smart Card Interface Speed	420 kbps
Smart Card Clock Frequency	up to 12 MHz
Smart Card detection	Movement detection with auto power-off; Automatic detection of smart card type; Short circuit and thermal protection
8-Pin Handling	C4 / C8 supported
USB Interface	HOST INTERFACE USB 2.0 Full Speed Device (12 MBps) USB 3.0 extended operability, tested with hubs/controllers
Connector / Cable	USB Type A connector; 59.1" (150 cm) cable
Operating Systems	Windows 10/8.1/8/7/Vista/Server 2012/Server 2008R2 Windows CE (5/6/7) depending on hardware Linux Debian 6.0+ / Ubuntu 11.04+ / Fedora 15+; Open SUSE 11.4+ Mac OS X; Android™
Driver	CCID native driver from operating system
Supported APIs	PC/SC - API
Status indicator	HUMAN INTERFACE Blue LED
Housing	HOUSING Transparent / grey polycarbonate
Dimensions	2.91" x 2.52" x 0.51" (74 x 64 x 13 mm)
Weight	1.69 oz (48g)
Operating Temperature	OPERATING CONDITIONS 32-131 F (0-55°C)
Operating Humidity	10-90% rH
Storage Temperature	-4 - 176 F (-20 - 80°C)
Meantime Between Failure (MTBF)	500,000 hours
Compliance / Certification	COMPLIANCE AND REGULATORY EMVCo Terminal Level 1 USB 2.0; TAA; GSA Fips 201 approved list
Regional certifications	CE, FCC, UL, VCCI, KCC, MIC, RCM (C-Tick)
Environmental	WEEE, RoHS, Reach
Warranty	OPERATING CONDITIONS Two-year manufacturer's warranty



hidglobal.com

North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

© 2017 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, and OMNIKEY are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks and product or service names are trademarks or registered trademarks of their respective owners.

2017-05-10-omnikey-3021-usb-reader-ds-en PLT-00308

An ASSA ABLOY Group brand

ASSA ABLOY